

# MATERIAL SAFETY DATA SHEET

HMIS HAZARDOUS MATERIALS

(Prepared According to 29 CFR 1910.1200)

A = Safety Glasses  
B = A + Gloves  
C = B + Apron  
D = C + Face Shield  
E = B + Dust Mask

F = C + Dust Mask  
G = B + Respirator  
H = F + Goggles  
I = B + Respirator  
X = Ask Supervisor

4 = Extreme  
3 = High  
2 = Moderate  
1 = Slight  
0 = Insignificant

IDENTIFICATION SYSTEM

Health.... 2  
Flammability.... 2  
Reactivity.... 0  
Protection.... A

## SECTION I - PRODUCT IDENTIFICATION

**Product Code: A622** Supersedes date: February 16, 1994 Section(s) changed: I, II, III, IV, VI, VII, VIII, IX, X Effective date: June 24, 2003

PRODUCT NAME: HI-GLOSS  
GENERIC NAME: Furniture Polish  
DISTRIBUTORS NAME:

CHEMICAL FAMILY: Furniture Polish Aerosol  
FORMULA: Proprietary Mixture  
DISTRIBUTORS ADDRESS:

INFORMATION PHONE NUMBER: 314-771-6600

EMERGENCY PHONE NUMBER IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING A SPILL, LEAK, FIRE OR ACCIDENT: CHEMTREC 800-424-9300

PROPER SHIPPING DESCRIPTION: Consumer Commodity, ORM-D

LABEL: None

## SECTION II - HAZARDOUS INGREDIENTS

| CHEMICAL NAME             | CAS No.    | Wt% | OSHA PEL | ACGIH TLV | OTHER |
|---------------------------|------------|-----|----------|-----------|-------|
| Hydrotreated Heavy Naptha | 64742-48-9 |     | NE       | 400 ppm   |       |
| Propane                   | 74-98-6    |     | 1000 ppm | 1000 ppm  |       |
| Isobutane                 | 75-28-5    |     | NE       | 800 ppm   |       |

The information & recommendations set forth herein are presented in good faith & believed to be current & reliable. The distributor makes no representation as to the completeness or accuracy thereof & supplies information upon the condition that the persons receiving same will make their own determination as to its suitability for their purpose prior to use. In no event will the distributor be responsible for any damage of any nature whatsoever resulting from the use of or reliance upon this information. No representation or warranty, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which it refers.

## SECTION III - PHYSICAL/CHEMICAL DATA

Boiling Point (°F): NE  
Vapor Pressure: 80 psig  
Evaporation Rate: (Butyl Acetate=1): <1  
Solubility in Water: Insoluble  
Physical Description: White - Lemon Odor

Specific Gravity: 0.90  
Vapor Density (Air=1): >1  
pH: N/A

## SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLAME PROJECTION: 12 inches  
FLASH POINT (Method Used): N/A  
EXTINGUISHING MEDIA: CO<sub>2</sub>, Standard Foam, Dry Chemical, Halon.  
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus.  
UNUSUAL FIRE & EXPLOSION HAZARD: Exposure to temperatures over 120°F may cause bursting or venting. Heat or fire may cause hazardous fumes: Carbon Monoxide.

## SECTION V - REACTIVITY DATA

Stability: Stable.  
Hazardous Polymerization: Will not occur.  
Incompatibility (Materials to Avoid): Oxidizing materials.  
Conditions to Avoid: Sources of heat.  
Hazardous Decomposition Products: Open flames may produce carbon monoxide.

## SECTION VI - STORAGE & HANDLING INFORMATION

KEEP OUT OF REACH OF CHILDREN. DANGER.  
Do not store where temperatures exceed 120°F.  
Do not get in eyes, on skin or on clothing.  
Wash hands before eating or smoking after using aerosol.

## SECTION VII - HEALTH HAZARDS AND FIRST AID

| Carcinogenicity:   | NTP?   | IARC Monographs? | OSHA REGULATED? |
|--|--|------------------|-----------------|
| NE   | NE   | NE               | NO              |
| EFFECTS OF OVEREXPOSURE:   | EMERGENCY FIRST AID PROCEDURES:  |                  |                 |
| SKIN: May cause itching, dryness, redness, or irritation.  | SKIN: Wash with soap & water. See physician if irritation persists.  |                  |                 |
| EYES: May cause irritation, redness, or watering.  | EYES: Flush with flowing water for 15 minutes. See physician if irritation persists.   |                  |                 |
| INHALATION: Large amounts of vapor may cause nausea, dizziness, headache and upper respiratory discomfort. | INHALATION: Remove to fresh air. Administer oxygen if breathing is difficult. If breathing has stopped, apply suitable artificial respiration. Get medical help. |                  |                 |
| INGESTION: Nausea, headache, vomiting.   | INGESTION: DO NOT induce vomiting. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.  |                  |                 |

## SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Not required.  
VENTILATION RECOMMENDED: General ventilation recommended to maintain the level of the hazardous ingredients to less than half of the TLV.  
PROTECTIVE GLOVES: Impervious rubber, for prolonged contact.  
EYE PROTECTION: Safety goggles, for prolonged contact.  
OTHER PROTECTIVE EQUIPMENT: None.

## SECTION IX - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Evacuate area. Remove all sources of ignition. Dike area if possible for material recovery. Small quantities may be absorbed with absorbent materials.  
WASTE DISPOSAL METHOD: Dispose of in accordance with applicable Federal, State & Local regulations.

## SECTION X - ADDITIONAL FEDERAL REGULATIONS

SARA TITLE III (EPCRA) NOTIFICATION: Does not contain chemicals subject to the reporting requirements of Section 302, 304, or 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986.  
COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT (CERCLA) NOTIFICATION: This does not contain chemicals subject to reporting under CERCLA  
CLEAN AIR ACT NOTIFICATION: ISOBUTANE, PROPANE [REPORTABLE UNDER SECTION 112(r) OF TITLE III OF THE CLEAN AIR ACT AMMENDMENT OF 1990  
For more information, consult 40 CFR parts 302, 355, 370, 372, and 40 CFR part 68.

NE - Not Established NA - Not Applicable GT - Greater Than

A Product Of: Intercon Chemical Company 1100 Central Industrial Drive, St. Louis, MO 63110